



- NOTES**
- 1.) UNITS MUST BE ATTACHED TO IN-PLANT COMPRESSED AIR SUPPLY FOR CLEANING MECHANISM TO FUNCTION (80 MAX psig CLEAN DRY AIR)
  - 2.) WELDED STEEL CONSTRUCTION OF 12 Gd. MILD STEEL.
  - 3.) FINISH: INDUSTRIAL GRADE CRIMSON RED INSIDE & OUT.
  - 4.) DUST TRAY CAPACITY: 1.75 CUBIC FT.
  - 5.) INLET COLLAR SIZES 6 IN. 8 IN.

**SPECIFICATIONS**  
 TOTAL VALVES, 1  
 TOTAL CARTRIDGES, 2  
 COMPRESSED AIR 1.0 SCF @80psi per sec.

FILE RP2 SPECIFICATION				TOLERANCES UNLESS OTHERWISE SPECIFIED 3 DEC. PLACES +/- .00 4 DEC. PLACES +/- .000 ANGLES 1/2° UNLESS NOTED OTHERWISE		 METAL-FAB FABRICATORS & WELDERS VICTORIA, B.C. CAN.	
DRW. BY MC	DATE 2-2-98	CHKD. BY JJ	DRW. NO. 11	SH. 1 OF 1	FWR. NO. L1582	REV. 1	